

Fig. 1
(Prior Art)



Fig. 2



Fig. 3



Fig. 4A



Fig. 4B



Fig. 4C



Fig. 4D



Fig. 4E



Fig. 5

49

```
1   module <memory_name>
    /* where <memory_name> is the RT-level name of the memory;                    */

2   CLASS = {REGISTER FILE, SRAM, DRAM];
3   FUNCTION = {RAM, CAM, FIFO};
4   WIDTH = <integer>;
    /* where integer indicates the data width of the memory.                      */
5   DEPTH = <integer>;
    /* where integer indicates the address depth of the memory.                   */

6   MIN_ADDRESS = <integer>;
7   MAX_ADDRESS = <integer>;
    /* The minimum and maximum addressable locations for read and write ports.    */
8   READ_ADDRESS = {decoded, encoded};
9   WRITE_ADDRESS = {decoded, encoded};
    /* Fully decoded and encoded address signals.                                 */

10  PORTS = {R=<integers>,W=<integer>,RW=<integer>,C=<integer>,S, R};
    /* Where R: read only ports, W: write only ports, RW: read and write ports,   */
    /* C: compare ports, S: set port, R: reset port                               */

11  WRITE_POLARITIES={WD^polarity, WA^polarity, WE^polarity, WCLK^polarity};
    /* polarity ={+, -}                                                           */
    /* WD+ | WD- : write data acts as an A | B phase latch                       */
    /* WA+ | WA- : write address acts as an A | B phase latch                    */
    /* WE+ | WE- : write enable acts as an A | B phase latch                     */
    /* WCLK+ | WCLK- : actual write occurs on the rising/falling edge             */

12  READ_POLARITIES={RD^polarity, RA^polarity, RE^polarity, RCLK^polarity};
    /* polarity ={+, -}                                                           */
    /*RD+ | RD- : read data acts as an A | B phase latch                         */
    /* RA+ | RA- : read address acts as an A | B phase latch                     */
    /* RE+ | RE- : read enable acts as an A | B phase latch                      */
    /* RCLK+ | RCLK- : read occurs on the rising/falling edge                     */

13  RR_RESOLUTION={R, X};
    /* where R : indicates that the location could be read                        */
14  WW_RESOLUTION={true, false};
    /* where true: indicates that two ports can write to the same location        */
15  PORT_ARBITRATION={port names};
    /* The order the port names appear in the list determines the dominant ports. */
16  RW_RESOLUTION={NW, XW, OW, XX, OX};
    /* where NW: reading new data and writing the data                            */
    /* XW: reading X and writing the data                                         */
    /* OW: reading old data and writing data                                      */
    /* XX: reading and writing Xs                                                 */
    /* OX: reading old data and writing X                                         */

17  endmodule;
```

Fig. 6



Fig. 7



Fig. 8